

Amendments to the claims:

1. (currently amended) A claw-pole rotor for an electrical machine, ~~in particular a rotary current generator,~~ having two pole wheels (26, 27), which each carry claw poles (28 and 29, respectively), which each originate in a plate region (50) and have a pole root (53), and on a circumference of the claw-pole rotor (20), claw poles (28, 29) of the pole wheels (26, 27) are located in alternation, and located between the claw poles or interstices (~~56~~ 90), and a claw pole (28, 29) has a radially outward-oriented cylindrical-jacketlike surface (43), by which a pivot axis (65) is defined, and a chamfer (68) extends on the one hand in a circumferential direction and on the other in an edge direction of a claw pole (28 and 29, respectively), ~~wherein~~ characterized in that the chamfer (68) has a center portion m in an the edge direction that intersects a transition plane (59) which demarcates the pole root (53) and the freely projecting part of the claw pole (28 and 29, respectively), and the center portion m amounts to 8/10 of the length, oriented in the edge direction, of the chamfer (68); and ~~wherein~~ that the claw pole (28, 29) has a width B_K oriented in the circumferential direction, and a half width B_K on the cylindrical surface (43), in a plane of the claw pole (28, 29) that is vertical to the pivot axis (65), defines a point (P), and a tangent (T) can be inscribed into said this point (P), and an angle of inclination α which has a magnitude of between 15° and 25° is enclosed between the tangent (T) and the chamfer (68) in the plane that is vertical to the pivot axis (65).

2. (currently amended) The claw-pole rotor as defined by claim 1, wherein
~~characterized in that~~ the center portion m amounts to 1/3 of the length (l) of the
chamfer (68).

3. (currently amended) The claw-pole rotor as defined by claim 1, wherein
~~characterized in that~~ the chamfer (68) has a center (m) in the edge direction that
is located close to the transition plane (59) from the pole root (53) to the freely
projecting part of the claw pole (28 and 29, respectively).

4. (currently amended) The claw-pole rotor as defined by claim 1, wherein
~~characterized in that~~ the chamfer (68) extends up to 5 mm in the pivot axis
direction (65) on the freely projecting part of the claw pole (28 and 29,
respectively).

5. (currently amended) The claw-pole rotor as defined by claim 4, wherein
~~characterized in that~~ the chamfer (68) extends up to 2 mm in the pivot axis
direction (65) on the freely projecting part of the claw pole (28 and 29,
respectively).

6. (currently amended) The claw-pole rotor as defined by claim 1, wherein
~~characterized in that~~ the chamfer (68) has a width (b_F) of between 4 mm and 6
mm.

7. (currently amended) The claw-pole rotor as defined by claim 1, wherein ~~characterized in that~~ the chamfer (68) has a length (l) of between 4 mm and 6 mm.

8. (currently amended) The claw-pole rotor as defined by claim 1, wherein ~~characterized in that~~ the chamfer (68) is a plane which is oriented parallel to the pivot axis direction (65) or parallel to the edge direction (73).

9. (currently amended) The claw-pole rotor as defined by claim 1, wherein ~~characterized in that~~ between the chamfer (68) and the cylindrical-jacketlike surface (43) is a stepped transition (80).

10. (currently amended) The claw-pole rotor as defined by claim 1, wherein ~~characterized in that~~ the chamfer (68) is formed integrally in non-metal-cutting fashion, in particular being forged on.

11. (currently amended) A rotary current generator[,] ~~in particular for motor~~ vehicles, having an annular-cylindrical stator iron (86) and having a claw-pole rotor (20) as defined by claim 1, wherein ~~characterized in that~~ the chamfers (68) project beneath the stator iron (86) in such a way that a portion of the chamfers (68) remains outside the stator iron (86).

12. (currently amended) The rotary current generator as defined by claim 11, ~~wherein characterized in that~~ the chamfers (68) project at least 1 mm beneath the stator iron (86).

13. (currently amended) The rotary current generator as defined by claim 11, ~~wherein characterized in that~~ the rotary current generator has a defined direction of rotation (D), in which the claw-pole rotor (20) is rotated to generate current, and each claw pole (28, 29) has one edge (73) that is oriented in the direction of rotation and one edge (70) that is oriented counter to the direction of rotation, and the chamfer (68) is located on the side of the claw pole (28, 29) that has the edge (73) that is oriented in the direction of rotation (D).